



GENERAL NOTES:

1. FOR RESIDENTIAL DEVELOPMENTS WITH AN ON-SITE STORM WATER CONTROL FACILITY, THE SUMP PUMP SHALL BE CONNECTED INTO THE STORM SEWER SYSTEM NOT LOCATED WITHIN THE PUBLIC RIGHT-OF-WAY.
2. ALL OTHER SUMP PUMP CONNECTIONS ARE TO SPLASH TO GRADE UNLESS WRITTEN APPROVAL IS GIVEN BY THE DIRECTOR OF PUBLIC WORKS.
3. SUMP PUMP DISCHARGE SHALL BE DIRECTED AWAY FROM ADJACENT PROPERTIES.
4. INSTALLER ASSUMES FULL RESPONSIBILITY AND LIABILITY FOR ANY AND ALL DAMAGE TO UTILITIES OR ADJOINING PROPERTIES.
5. INSTALLATION OF SUMP PUMP DRAIN TILES MUST BE INSPECTED BY THE CITY OF WOOD DALE.
6. SLOTTED GRATE ON UPTURNED TEE SHALL BE 12" BELOW ENTRANCE POINT.
7. SEE STORM 11 FOR TRENCH SECTION.

END OF TEE WRAPPED IN GEOTEXTILE FABRIC AND PLACED IN FABRIC-LINED 1 CUBIC YARD DRY WELL.

REV.:	REV.:
REV.:	REV.:
DRAWN BY:	DATE: 4-3-18

**SUBSURFACE DRAIN TILE
SUMP PUMP CONNECTION**

CITY OF WOOD DALE
STORM 10A